

ETHERLINE® ACCESS M05T/M08T

Managed switches for industrial communication

Industrial network switches for ethernet based solutions in Smart Factories.

Info

Redundant power inputs

Robust metal housing and DIN rail mounting

Fanless – maintenance free



Mechanical and plant engineering



Automation & fältinstallation

Benefits

Improve your total cost of ownership with faster installation and lower downtime

Most flexible and globally present solutions from one hand

Product features

Simple setup of redundant networktopologies with reconfiguration time < 20 ms

RJ45 Ports: 10/100BaseT(X)

Packet Buffer Size: 1 Mbit

Supported protocols: HTTP, Telnet, EtherNet/IP, Modbus/TCP, IPv6, and many more

Redundant Power Input: 24 VDC

Norm references / Approvals

Shock IEC 60068-2-27

Freefall IEC60068-2-32

Vibration IEC 60068-2-6

Last Update (25.12.2017)

©2017 Lapp Group - Technical changes reserved

Product Management www.lappkabel.de

You can find the current technical data in the corresponding data sheet.

PN 0456 / 02_03.16

ETHERLINE® ACCESS M05T/M08T**Technical Data**

| | |
|------------------------|---|
| Classification ETIM 5: | ETIM 5.0 Class-ID: EC000734 ETIM 5.0 Class-Description: Network switch |
| Classification ETIM 6: | ETIM 6.0 Class-ID: EC000734 ETIM 6.0 Class-Description: Network switch |
| Protection rating: | IP 30 |
| Temperature range: | 0°C to +60°C |

Note

Photographs and graphics are not to scale and do not represent detailed images of the respective products.
Prices are net prices without VAT and surcharges. Sale to business customers only.



ETHERLINE® ACCESS M05T/M08T

| Article number | Article designation | Type | RJ45 ports | MTBF in years |
|----------------|------------------------|---------|------------|---------------|
| 21700121 | ETHERLINE® ACCESS M05T | Managed | 5 | > 97 |
| 21700122 | ETHERLINE® ACCESS M08T | Managed | 8 | > 125 |

Last Update (25.12.2017)

©2017 Lapp Group - Technical changes reserved

Product Management www.lappkabel.de

You can find the current technical data in the corresponding data sheet.

PN 0456 / 02_03.16