



## UNITRONIC® 100

Control and signal cable with small cross-sections



### Info

- UNITRONIC® colour code with protective conductor

## UNITRONIC® 100 CY

Screened control and signal cable with small cross-sections



### Application range

- These control and signal cables are used in the milliamperage range for computer systems, electronic control equipment, office machines, balances etc. and wherever the thinnest possible control cables are required.

### Product features

#### UNITRONIC® 100

- Robust, flexible and resistant outer sheath
- Small outer diameter despite high number of cores
- Flame-retardant according IEC 60332-1-2
- 3 cores with earth wire (green-yellow)  
2 cores (black/blue)

#### UNITRONIC® 100 CY

- Robust, flexible and resistant outer sheath
- Small outer diameter despite high number of cores
- Cable similar to UNITRONIC® 100, but with copper braiding
- Flame-retardant according IEC 60332-1-2
- 3 cores with earth wire (green-yellow)  
2 cores (black/blue)

### Norm references / Approvals

- Based on: VDE 0814 or VDE 0812

### Product Make-up

#### UNITRONIC® 100

- Fine-wire/multi-wire (0.34 mm<sup>2</sup>) strand made of bare copper wires
- Core insulation made of PVC
- Outer sheath made of PVC  
Outer sheath colour: grey (RAL 7001)

#### UNITRONIC® 100 CY

- Fine-wire/multi-wire (0.34 mm<sup>2</sup>) strand made of bare copper wires
- Core insulation made of PVC
- Inner sheath made of PVC
- For the cross section of 0.14 mm<sup>2</sup>, a polyester tape is used underneath the screen braiding instead of the inner sheath.
- Tinned-copper braiding
- Outer sheath made of PVC  
Outer sheath colour: grey (RAL 7001)

### Technical data



#### Classification

ETIM 5.0 Class-ID: EC000830  
ETIM 5.0 Class-Description: Data cable



#### Core identification code

Refer to Appendix T7 for the UNITRONIC® colour codes



#### Mutual capacitance

Approx. 120 nF/km



#### Peak operating voltage

(not for power applications)  
500 V



#### Inductivity

approx. 0.7 mH/km



#### Conductor stranding

Stranded, fine-wire  
0.34 mm<sup>2</sup>: 7-wire



#### Minimum bending radius

##### UNITRONIC® 100

Occasional flexing: 15 x outer diameter  
Fixed installation: 4 x outer diameter

##### UNITRONIC® 100 CY

Occasional flexing: 20 x outer diameter  
Fixed installation: 6 x outer diameter



#### Test voltage

Core/core: 1500 V rms  
Core/screen: 1500 V



#### Protective conductor

Green-yellow



#### Temperature range

Occasional flexing: -5°C to +70°C  
Fixed installation: -40°C to +80°C

Article number	Number of cores and mm <sup>2</sup> per conductor	Outer diameter (mm)	Copper index (kg/km)	Weight (kg/km)
<b>UNITRONIC® 100</b>				
0028009	2 x 0,14	3	2.8	12
0028010	3 x 0,14	3.2	4.2	17
0028012	5 x 0,14	3.7	7	22
0028014	7 x 0,14	4	9.8	27
0028015	10 x 0,14	5	14	41
0028019	24 x 0,14	7.2	33.6	94
0028025	52 x 0,14	10	72.8	198
0028030	3 x 0,25	3.8	7.5	21
0028031	7 x 0,25	4.9	17.5	48
0028032	10 x 0,25	6.4	25	77
0028033	14 x 0,25	6.9	35	95
0028034	16 x 0,25	7.3	40	112
0028035	21 x 0,25	8.5	52.5	139
0028036	24 x 0,25	9	60	163
0028037	27 x 0,25	9.2	67.5	171

Article number	Number of cores and mm <sup>2</sup> per conductor	Outer diameter (mm)	Copper index (kg/km)	Weight (kg/km)
0028038	30 x 0,25	9.9	75	187
0028039	36 x 0,25	10.7	90	235
0028040	40 x 0,25	11.6	100	266
0028042	52 x 0,25	12.5	130	343
0028044	61 x 0,25	13.3	152.5	398
0028047	3 x 0,34	4.2	10.5	33
0028048	7 x 0,34	5.5	22.8	62
0028051	16 x 0,34	8.3	54.4	131
<b>UNITRONIC® 100 CY</b>				
0034006	2 x 0,14	3.7	12	20
0034007	3 x 0,14	3.9	13	28
0034008	4 x 0,14	4.1	14.3	33
0034009	5 x 0,14	4.4	15.5	38
0034010	7 x 0,14	4.7	20.3	49
0034011	10 x 0,14	5.7	34.3	66
0034012	14 x 0,14	6.3	32	80
0034013	16 x 0,14	6.6	40.9	90
0034016	27 x 0,14	8.1	70.6	148
0031031	3 x 0,25	5.4	20.2	48
0031066	4 x 0,25	5.7	24	61
0031067	5 x 0,25	6.3	29	72
0031032	7 x 0,25	6.7	37.6	82
0031033	10 x 0,25	8.2	48.8	129
0031034	14 x 0,25	8.7	64.6	147
0031068	2 x 0,34	5.6	20	45
0031048	3 x 0,34	5.8	24.1	62
0031069	4 x 0,34	6.4	29	65
0031070	5 x 0,34	6.9	42	95
0031049	7 x 0,34	7.3	50	106
0031050	10 x 0,34	9	67.7	167
0031052	16 x 0,34	10.5	95	219
0031060	52 x 0,34	17.6	336	629

Unless specified otherwise, the shown product values are nominal values. Detailed values (e.g. tolerances) are available upon request.  
 Copper price basis: EUR 150/100 kg. Refer to catalogue appendix T17 for the definition and calculation of copper-related surcharges.  
 Please find our standard lengths at: [www.lappkabel.de/en/cable-standardlengths](http://www.lappkabel.de/en/cable-standardlengths)  
 Packaging size: coil ≤ 30 kg or ≤ 250 m, otherwise drum  
 Please specify the preferred type of packaging (e.g. 1 x 500 m drum or 5 x 100 m coils).  
 Photographs are not to scale and do not represent detailed images of the respective products.

**Similar products**

- UNITRONIC® LiYY refer to page 278
- UNITRONIC® LiYCY refer to page 279

**Accessories**

- UNIVERSAL STRIP stripping tool refer to page 1006
- STAR STRIP stripping tool refer to page 1000