

Ethernet Cable

NEED CUSTOMS?
See Page 25

Cat 5e

- Ideal for Motion and Harsh Environment Applications
- Exceeds ANSI/TIA/EIA-568-A and TIA/EIA-568-B Cat 5e Specs
- Supporting Data Rates to 1 Gb/second

Cat 6

- Meets or Exceeds Cat 6 - EIA/TIA-568-C/ 11801
- Provide Stringent Crosstalk/Noise Suppression
- Flat Cable Delivers Highest Data Speeds

Cicoil's ethernet cables meet the increased demand of professionals who need a rugged, reliable, portable, flexible and harsh environment ready network cable solution. Cicoil's patented extrusion process allows individually shielded wires to be placed in a highly flexible flat profile for clear, high speed data transmission.



Applications
PLC and DCS Automation Networks, Field Level Networking and Ethernet Networks

Cable


Type	Amp Rating ¹	Conductor Gauge	No. of Pairs	Dimensions [inches]		Part Number
				Width	Height	
Cat 5e	3	30 AWG	4	0.45	0.14	DC-500
Cat 6	7	24 AWG	4	0.71	0.20	DC-600

Note


1. Amp rating is the maximum value for each conductor at room temperature of 70°F (21°C). Amp rating decreases as temperature increases.

Dimensions

Cat 5e



Cat 6



Cable Assemblies




Cable Length (feet)	Part Number Addition
3	-CA003
6	-CA006
12	-CA012

Notes

1. Append onto base cable Part Number for complete assembly. Example: DC-500-CA003
2. Connector ratings may differ from cable ratings; refer to manufacturer specifications.

Please contact Cicoil for other connectors and length options.

Assembly Dimensions



Connectors

- Signal (J1): RJ45

Cable Specifications

All engineering values are nominal and subject to change.

Mechanical	Environmental
Conductors: Ultra flexible, finely stranded, tinned copper	Temperature Rating: -65°C to +165°C
Shielding: Ultra flexible, braided shields, with 90% nominal coverage	Moisture Rating: Submersible, Salt Water Resistant
Minimum Bend Radius:	Clean Room Rating: Class 1, Zero Particulates
- 6x cable height for intermediate flex	Extreme Environments: Sunlight, UV Light, Alcohol, Chemical and Oil Resistant
- 10x cable height for continuous flex	Electrical
Flex Life: 10,000,000 cycles nominal	Outer Jacket Dielectric Strength: 450 volts/mil (17.7 kv/mm)
Outer Jacket Durometer Rating: 65 (Shore A)	See Electrical Rating Chart on Page 47

Options

Page

Additional Conductors	26
Low Friction Options	28
StripMount™ Integrated Mounting Strip	28
Integrated Tubing	29
SuperTuff™ Jacket	29
Colored Jacketing	29
Strip and Tin Cable Ends	29
FlexRail™ Self-Supporting Cable	30
Complete Assembly	31