



SKINDICHT® MR-M



Benefits

- Enables the use of cable glands with smaller connection threads than the existing threaded holes

Application range

- Machines
- Devices
- Housings

Product Make-up

- Metric connection thread acc. to DIN EN 60423
- Basis for technical information EN 50262

Note

- Drawing on request

Technical data

Classification
 ETIM 5.0 Class-ID: EC000441
 ETIM 5.0 Class-Description:
 Cable screw gland

On request
 Also available with pre-installed O-ring

Material
 Nickel-plated brass

Temperature range
 -60°C to +200°C

Article number	Thread, male M1	Thread, female M2	Overall length, C (mm)	Thread length, D (mm)	Outer Ø (mm)	Pieces / PU
SKINDICHT® MR-M						
52104310	16 x 1.5	12 x 1.5				100
52104311	20 x 1.5	12 x 1.5				100
52104312	20 x 1.5	16 x 1.5				100
52104313	25 x 1.5	16 x 1.5				50
52104314	25 x 1.5	20 x 1.5				50
52104315	32 x 1.5	20 x 1.5				50
52104316	32 x 1.5	25 x 1.5				50
52104317	40 x 1.5	25 x 1.5				25
52104318	40 x 1.5	32 x 1.5				25
52104319	50 x 1.5	32 x 1.5				25
52104320	50 x 1.5	40 x 1.5				10
52104321	63 x 1.5	40 x 1.5				10
52104322	63 x 1.5	50 x 1.5				10
SKINDICHT® MR-M, blank brass						
52006579	80 x 2	75 x 1.5	19.0	12	86.0	1
SKINDICHT® MR-M, nickel-plated brass						
52006575	72 x 2	63 x 1.5	19.0	12	78.0	1

Photographs are not to scale and do not represent detailed images of the respective products.

ÖLFLEX®
 UNITRONIC®
 ETHERLINE®
 HITRONIC®
 EPIC®
 SKINTOP®
 SILVYN®
 FLEXIMARK®
 ACCESSORIES
 APPENDIX