



## SKINTOP® BRUSH ADD-ON



### Benefits

- Optimum, low-resistance 360° screen contact
- Cutting edges cut through the insulating layer of the housing or switch cabinets, thus guaranteeing an optimum EMC contact
- Easy disassembling
- Visible, large-scale screen contact
- Uncomplicated and reliable

### Application range

- For EMC-compliant earthing of the copper braiding, or for cables with copper shaft sheath
- For EMC-contact at through bore-holes
- Control cabinet manufacturing
- Automation systems
- Conveyor and transport systems

### Product Make-up

- Metric connection thread acc. to DIN EN 60423
- Basis for technical information EN 50262



### Info

- Innovative EMC add-on for SKINTOP® ST(R)-M polyamide cable glands.
- Worlds first patented active EMC lock-nut!

### Technical data



#### Classification

ETIM 5.0 Class-ID: EC000441  
ETIM 5.0 Class-Description:  
Cable screw gland



#### Caution

Refer to Appendix T21 for the installation dimensions and torques  
Apply SKINTOP® ST-M torques



#### Certifications

UL pending



#### Material

Body: nickel-plated brass  
EMC brush: brass



#### Temperature range

Dynamic: -20°C to +100°C  
Depending on the combination of the used cable gland

Article number	Article designation / size	Minimum Ø above braiding (mm)	SW wrench size mm	Thread length, D (mm)	Pieces / PU
<b>SKINTOP® BRUSH ADD-ON</b>					
54110839	M 12 x 1,5	4	24	10	25
54110840	M 16 x 1,5	5	24	10	25
54110841	M 20 x 1,5	5	24	10	10
54110842	M 25 x 1,5	5	30	10	10
54110843	M 32 x 1,5	8	39	12	10
54110844	M 40 x 1,5	10	47	12	5
54110845	M 50 x 1,5	14	56	12	5
54110846	M 63 x 1,5	14	63	12	5

Photographs are not to scale and do not represent detailed images of the respective products.

### Accessories

- SKINTOP® BS-M refer to page 719
- SKINTOP® ST-M refer to page 712
- SKINTOP® STR-M refer to page 712
- SKINTOP® ST-HF-M refer to page 718
- SKINTOP® COLD refer to page 727
- SKINTOP® COLD-R refer to page 727

