




SKINDICHT® SVF-M



Benefits

- Lateral sealing lips fit automatically around various cable dimensions
- Cable-specific seal dimensions are no longer necessary
- Large opening allows clamping of up to two flat cables
- Optimum strain relief
- Tolerance

Application range

- For inserting flat cables
- Control cabinet manufacturing
- Conveyor systems
- Pumps
- Lifts

Product Make-up

- Metric connection thread acc. to DIN EN 60423
- Basis for technical information EN 50262

Note

- For suitable flat cables, refer to ÖLFLEX® LIFT F for indoor applications or ÖLFLEX® CRANE F for outdoor applications
- Counter nut to be used: SKINDICHT® SM-M

Technical data

- Classification**
ETIM 5.0 Class-ID: EC000441
ETIM 5.0 Class-Description: Cable screw gland
- Caution**
The installation dimensions can be found in appendix T21
- Material**
Body: nickel-plated brass
Seal: CR
- Protection rating**
IP 54
- Temperature range**
-30°C to +100°C

| Article number | Article designation / size | Min./max. flat cable width | Min./max. cable thickness (mm) | Pieces / PU |
|-------------------------|----------------------------|----------------------------|--------------------------------|-------------|
| SKINDICHT® SVF-M | | | | |
| 52107320 | M 20/16 | - / 15.0 | - / 5 | 25 |
| 52107340 | M 25/21 | 9.0 / 20.0 | 3 / 8 | 25 |
| 52107350 | M 32/29 | 14.0 / 27.0 | 4 / 11 | 10 |
| 52107360 | M 40/36 | 24.0 / 34.0 | 4 / 11 | 10 |
| 52107370 | M 50/42 | 29.0 / 44.0 | 5 / 12 | 5 |
| 52107380 | M 63/48 | 34.0 / 50.0 | 5 / 12 | 5 |

Photographs are not to scale and do not represent detailed images of the respective products.