


# Motor cable | PVC | chainflex® CF31

- For heavy duty applications
- PVC outer jacket
- Shielded
- Oil-resistant
- Flame retardant



## Dynamic information

	<b>Bend radius</b>	<b>e-chain® linear flexible</b>	minimum 7.5 x d minimum 6 x d
	<b>Temperature</b>	<b>e-chain® linear flexible</b>	+5 °C to +70 °C -5 °C to +70 °C (following DIN EN 60811-504)
		<b>fixed</b>	minimum 4 x d -15 °C to +70 °C (following DIN EN 50305)
	<b>v max.</b>	<b>unsupported</b>	10 m/s
	<b>a max.</b>	<b>gliding</b>	5 m/s
	<b>Travel distance</b>	Unsupported travel distances and up to 100 m for gliding applications, Class 5	

## Cable structure

	<b>Conductor</b>	<b>Cores &lt; 10 mm²:</b> Stranded conductor in especially bending-resistant design consisting of bare copper wires (following DIN EN 60228). <b>Cores ≥ 10 mm²:</b> Conductor consisting of pre-wound conductor bundles (following DIN EN 60228).
	<b>Core insulation</b>	Mechanically high-quality, especially low-capacitance TPE mixture.
	<b>Core structure</b>	Cores wound with a short pitch length around a high tensile strength centre element.
	<b>Core identification</b>	Black cores with white numerals, one core green-yellow. 1. Core: U / L1 / C / L+ 2. Core: V / L2 3. Core: W / L3 / D / L- 4. Core: 4 / N
	<b>Inner jacket</b>	PVC mixture, adapted to suit the requirements in e-chains®.
	<b>Overall shield</b>	Extremely bending-resistant braiding made of tinned copper wires. Coverage approx. 70 % inear, approx. 90 % optical
	<b>Outer jacket</b>	Low-adhesion, oil-resistant PVC mixture, adapted to suit the requirements in e-chains® (following DIN EN 50363-4-1). Colour: Jet black (similar to RAL 9005)
	<b>CFRIP®</b>	Strip cables faster: a tear strip is moulded into the inner jacket Video ► <a href="http://www.igus.eu/CFRIP">www.igus.eu/CFRIP</a>

## Electrical information

	<b>Nominal voltage</b>	600/1000 V (following DIN VDE 0298-3)
	<b>Testing voltage</b>	4000 V (following DIN EN 50395)

# Class 5.5.2.1

Basic requirements	low	1	2	3	4	5	6	7	highest
Travel distance	unsupported	1	2	3	4	5	6	≥ 400 m	
Oil resistance	none	1	2	3	4	highest			
Torsion	none	1	2	3	±180°				

## Properties and approvals

	<b>UV resistance</b>	Medium.
	<b>Oil resistance</b>	Oil-resistant (following DIN EN 50363-4-1), Class 2.
	<b>Flame retardant</b>	According to IEC 60332-1-2, CEI 20-35, FT1, VW-1
	<b>Silicone-free</b>	Free from silicone which can affect paint adhesion (following PV 3.10.7 – status 1992).
	<b>UL/CSA</b>	Style 10492 and 2570, 1000 V, 80 °C
	<b>NFFPA</b>	Following NFPA 79-2012 chapter 12.9.
	<b>EAC</b>	Certificate no. RU C-DE.ME77.B.02324 (TR ZU)
	<b>CTP</b>	Certificate no. C-DE.PB49.B.00420 (Fire safety)
	<b>CEI</b>	Following CEI 20-35.
	<b>Lead-free</b>	Following 2011/65/EU (RoHS-II).
	<b>Cleanroom</b>	According to ISO Class 2. Outer jacket material complies with CF5.10.07, tested by IPA according to standard 14644-1.
	<b>CE</b>	Following 2014/35/EU.

## Guaranteed lifetime according to guarantee conditions (Page 22-23)

Double strokes*	5 million	7.5 million	10 million
Temperature, from/to [°C]	R min. [factor x d]	R min. [factor x d]	R min. [factor x d]
+5/+15	10	11	12
+15/+60	7.5	8.5	9.5
+60/+70	10	11	12

\* Higher number of double strokes? Online lifetime calculation: [www.igus.eu/chainflexlife](http://www.igus.eu/chainflexlife)

## Typical mechanical application areas

- For heavy duty applications
- Light oil influence
- Preferably indoor applications, but also outdoor ones at temperatures > 5 °C
- Unsupported travel distances and up to 100 m for gliding applications
- Storage and retrieval units for high-bay warehouses, machining units/ packaging machines, quick handling equipment, indoor cranes



Example image

# Motor cable | PVC | chainflex® CF31

Strip cables 50% faster

## Class 5.5.2.1

Basic requirements  
Travel distance  
Oil resistance  
Torsion

low	1	2	3	4	5	6	7	highest
unsupported	1	2	3	4	5	6	≥ 400 m	
none	1	2	3	4	highest			
none	1	2	3	±180°				

igus® chainflex® CF31

Example image

Part No.	Number of cores and conductor nominal cross section [mm²]	Outer diameter (d) max. [mm]	Copper index [kg/km]	Weight [kg/km]
CF31.15.04	(4G1.5)C	10.5	94	168
CF31.25.04	(4G2.5)C	12.0	142	233
CF31.25.05	(5G2.5)C	13.0	174	295
CF31.40.04	(4G4.0)C	13.5	217	345
CF31.40.05	(5G4.0)C	15.0	281	424
CF31.60.04	(4G6.0)C	16.0	318	488
CF31.60.05	(5G6.0)C	18.0	385	598
CF31.100.04	(4G10.0)C	20.5	539	833
CF31.100.05	(5G10.0)C	22.5	687	954
CF31.160.04	(4G16.0)C	23.5	823	1127
CF31.250.04	(4G25.0)C	28.5	1254	1718
CF31.350.04	(4G35.0)C	32.5	1716	2298
CF31.500.04	(4G50.0)C	37.5	2420	3173
CF31.700.04	(4G70.0)C	43.0	3454	4085

Note: The given outer diameters are maximum values and may tend toward lower tolerance limits.  
G = with green-yellow earth core x = without earth core



Order example: **CF31.15.04** – to your desired length (0.5 m steps)  
CF31 chainflex® series .15 Code nominal cross section .04 Code Number of cores



Online order ► [www.chainflex.eu/CF31](http://www.chainflex.eu/CF31)



Delivery time 24h or today.  
Delivery time means time until shipping of goods.

