










Spindle cable/Single core | PVC | chainflex® CF886

- For flexing applications
- PVC outer jacket
- Shielded
- Flame retardant



Dynamic information

 Bend radius	e-chain® linear flexible fixed	minimum 15 x d minimum 12 x d minimum 8 x d
 Temperature	e-chain® linear flexible fixed	+5 °C to +70 °C -5 °C to +70 °C (following DIN EN 60811-504) -15 °C to +70 °C (following DIN EN 50305)
 v max.	unsupported	3 m/s
 a max.		20 m/s ²
 Travel distance		Unsupported travel distances up to 10 m, Class 1

Cable structure








 Conductor	Conductor consisting of bare copper wires (following DIN EN 60228).	
 Core insulation	Mechanically high-quality PVC mixture.	
 Overall shield	Braiding made of tinned copper wires. Coverage approx. 60 % optical	
 Outer jacket	Low-adhesion PVC mixture, adapted to suit the requirements in e-chains®. Colour: Pastel orange (similar to RAL 2003)	

Electrical information

 Nominal voltage	600/1000 V (following DIN VDE 0298-3)	
 Testing voltage	4000 V (following DIN EN 50395)	

Class 3.1.1.1

Properties and approvals

 Flame retardant	According to IEC 60332-1-2, CEI 20-35, FT1, VW-1
 Silicone-free	Free from silicone which can affect paint adhesion (following PV 3.10.7 – status 1992).
 UL/CSA	Style 10107, 600 V, 80 °C
 EAC	Certificate no. RU C-DE.ME77.B.01561 (TR ZU)
 CTP	Certificate no. C-DE.PB49.B.00450 (Fire safety)
 Lead-free	Following 2011/65/EU (RoHS-II).
 CE	Following 2014/35/EU.

Guaranteed lifetime according to guarantee conditions (Page 22-23)

Double strokes*	1 million	3 million	5 million
Temperature, from/to [°C]	R min. [factor x d]	R min. [factor x d]	R min. [factor x d]
+5/+15	17.5	18.5	19.5
+15/+60	15	16	17
+60/+70	17.5	18.5	19.5

* Higher number of double strokes? Online lifetime calculation: www.igus.eu/chainflexlife

Typical mechanical application areas

- For flexing applications
- Without influence of oil
- Preferably indoor applications
- Especially for unsupported travels
- Wood/stone processing, Packaging industry, supply systems, Handling, adjusting equipment

Part No.	Number of cores and conductor nominal cross section [mm ²]	Outer diameter (d) max. [mm]	Copper index [kg/km]	Weight [kg/km]
CF886.100.01	(1x10.0)C	10.0	117	187
CF886.160.01	(1x16.0)C	11.5	180	256
CF886.250.01	(1x25.0)C	13.0	271	361
CF886.350.01	(1x35.0)C	15.5	382	521
CF886.500.01	(1x50.0)C	17.5	535	692
CF886.700.01	(1x70.0)C	19.5	737	917
CF886.950.01	(1x95.0)C	21.0	977	1159

Note: The given outer diameters are maximum values and may tend toward lower tolerance limits.
G = with green-yellow earth core x = without earth core



Example image

