



SKINDICHT® BL-M



Benefits

- For closing pre-threaded holes

Application range

- Machine and equipment manufacturing
- Electric motor manufacturing

Product features

- Assembling with screwdriver

Product Make-up

- Metric connection thread acc. to DIN EN 60423
- Basis for technical information DIN IEC 62444

Technical data

	Classification ETIM 5/6 ETIM 5.0/6.0 Class-ID: EC000032 ETIM 5.0/6.0 Class-Description: Plug for cable screw gland
	Certifications UL pending
	On request Fitted with FKM O-ring (-20°C to +200°C)
	Material Body: nickel-plated brass O-ring: NBR
	Protection rating IP 54 IP 68 (with O-ring)
	Temperature range With O-ring: -20°C to +100°C Without O-ring: -60°C to +200°C

Article number	Article designation / size	Overall length C mm	Thread length D mm	Outer Ø (mm)	Pieces / PU
SKINDICHT® BL-M					
52103100	M 12 x 1,5	7.5	5	14.0	100
52103110	M 16 x 1,5	8.0	5	18.0	100
52103120	M 20 x 1,5	9.5	6	22.0	100
52103130	M 25 x 1,5	11.0	7	28.0	100
52103140	M 32 x 1,5	12.0	8	35.0	50
52103150	M 40 x 1,5	13.0	9	44.0	25
52103160	M 50 x 1,5	15.0	9	54.0	10
52103170	M 63 x 1,5	16.0	10	70.0	10
52103190	M 75 x 1,5	17.0	11	80.0	1
SKINDICHT® BL-M with O-ring					
52103105	M 12 x 1,5	7.5	5	14.0	100
52103115	M 16 x 1,5	8.0	5	18.0	100
52103125	M 20 x 1,5	9.5	6	22.0	100
52103135	M 25 x 1,5	11.0	7	28.0	100
52103145	M 32 x 1,5	12.0	8	35.0	50
52103155	M 40 x 1,5	13.0	9	44.0	25
52103165	M 50 x 1,5	15.0	9	54.0	10
52103175	M 63 x 1,5	16.0	10	70.0	10

Photographs and graphics are not to scale and do not represent detailed images of the respective products.

Accessories

- SKINDICHT® SM-M refer to page 742
- SKINDICHT® O-ring FKM metric refer to page 757
- SKINDICHT® O-Ring NBR metric refer to page 757