



## SKINDICHT® VENT INOX



### Info

- Breathable pressure compensation element with membrane technology

### Benefits

- Ventilation system for housing
- Formation of condensation in electronic housings is prevented
- Pressure compensation elements guarantee a trouble-free and maintenance-free operation

### Application range

- Lighting engineering
- Railway applications
- Weather station
- Manufacturing of control cabinets and equipment
- Housing and distribution boxes

### Product features

- Closure element and a pressure equalization in one system
- Lower space requirement
- High air flow

### Norm references / Approvals

- Optionally approved acc. to UL 508 A

### Product Make-up

- Air flow rates: 100mbar=0.4 l/min - Standard version
- Air flow rates: 100mbar=2.4 l/min - UL version

### Note

- Refer to data sheet for more details

### Technical data

**Classification ETIM 5/6**  
 ETIM 5.0/6.0 Class-ID: EC000441  
 ETIM 5.0/6.0 Class-Description: Cable screw gland

**Certifications**  
 Metric thread acc. to EN 60423

**Note**  
 Membrane: Acryl - copolymere

**Material**  
 Stainless steel 303  
 O-ring - NBR

**IP Protection rating**  
 Standard: IP66 / IP68 / IP69  
 UL: IP66 / IP67 / IP69

**Temperature range**  
 -40 °C to +105 °C

Article number	Article designation / size	Overall length C mm	Thread length D mm	Pieces / PU
<b>Not certified version</b>				
51730204	SKINDICHT® VENT INOX 12x1,5	21.0	10	10
<b>cURus certified version</b>				
51730205	SKINDICHT® VENT INOX 12x1,5 plus	21.0	10	10

Photographs and graphics are not to scale and do not represent detailed images of the respective products.