

# Treoflex SDI-VSD Single Core VSD Cable



## Technical Data

Special screened single core for EMC applications

- **Temperature range**  
Flexing -30°C to + 90°C  
fixed installation -40°C to + 100°C
- **Nominal Voltage**  
U<sup>o</sup>/U 600/1000 V  
Test voltage 3000 V
- **Insulation resistance**  
min 200 MOhm x km
- **Minimum bending radius**  
fixed installation 5x cores Ø  
wetting properties of lacquers

## Cable Structure

- Tinned copper, fine wire conductors bunch stranded to DIN VDE 0295 class 5
- Inner insulation of special thermoplastic

## Properties

- Very good oil resistance
- Halogen free
- Abrasion resistant
- **Resistant to**  
Hydrofluoric acid  
Hydrochloric acid  
Diluted sulfuric acid  
Coolants  
Microbes  
UV-Radiation  
Weather
- The materials used in manufacture are cadmium-free and contain no silicone and are free from substances harmful to the wetting properties of lacquers.

## Application

The special single cores are used for permanent flexible applications in machines, machine tools, composting appliances and sewerage-treatment plants, animal stalls and greenhouses. They are used for permanent flexible application for movable automated machinery parts and multi-shift operation, as well as in open air. These cables are installed for flexible use with free movements without tensile stress or forced movements and are suitable for application in drag chains. The selected tinned copper wire conductor and tinned copper wire braid permit the installation in aggressive environments as well as hydrogen sulfide, ammonia and sulfur dioxide.

## TREFLEX - VSD

These screened cables are particularly suitable for the interference-free transmission instrumentation and control engineering applications (electromagnetic compatibility).

## EMC = Electromagnetic compatibility.

For application as a protective core, the ends are to be identified with green-yellow shrink-on tubes.

For applications which go beyond standard solutions (for example for composting appliances or high shelf conveyors with extremely high processing speeds etc). We recommend for our specially developed enquiry sheet for energy guiding systems.

Before installation in cable trays please read the instructions. For further technical details see selection table for drag chain cables, see lead text.

Part Number	No. of cores x cross-sec. mm <sup>2</sup>	Outer Ø ca. mm	Cop.weight kg/km	Weight kg/km
TA1.1200.01	1 x 120	23.8	1260.0	1400.0
TA1.1500.01	1 x 150	26.0	1570.0	1710.0
TA1.1850.01	1 x 185	28.8	1911.0	2021.0
TA1.2400.01	1 x 240	32.0	2475.0	2750.0
TA1.3000.01	1 x 300	36.5	3050.0	3450.0