






Ten 47 - Powerline, single pole, 400Amp

PANEL SOCKET (Panel Source)








400 Amp Panel Socket	Part Code		
	PSF -E-GN-T ⁴ -FP		Green
	PSF -N-BK-T ⁴ -FP		Black
	PSF -1-R-T ⁴ -FP		Red
	PSF -2-WH-T ⁴ -FP		White
	PSF -3-BU-T ⁴ -FP		Blue

Style "PSF"

Panel Source Connectors are typically used as the Live or Supply side of the circuit and utilise a Solid Insulated contact tip to provide IP2X Finger Protection when unmated. "PSF" Connectors incorporate a slot that engages with the Locking Pin on both the mating Panel Inlet and Cable Plug connectors.

PANEL INLET (Panel Drain)



400 Amp Panel Inlet	Part Code		
	PIF -E-GN-T ⁴ -FP		Green
	PIF -N-BK-T ⁴ -FP		Black
	PIF -1-R-T ⁴ -FP		Red
	PIF -2-WH-T ⁴ -FP		White
	PIF -3-BU-T ⁴ -FP		Blue

Style "PIF"

Panel Drain Connectors utilise a spring-mounted contact with a Double Insulated Sleeve that provides IP2X Finger Protection when unmated. The "CCF" contact depresses the spring and sleeves to obtain Electrical connection. When unmated, they return automatically to the IP2X position. A Locking Pin engages with the slot on both the Panel Socket and Cable Connectors when mated.

5

